

TECHNICAL DATA SHEET

Pergo Gotland

Edition

03.2016

PERGO

WOOD PARQUET®

General data

Panel	1820 x 190 mm
Total thickness	14 mm
Numbers of panels per pack	6
m ² per pack	2,08 m ²

Panel build up

Toplayer	PEFC controlled sources	3,2 mm
Core board		Hevea
Backing layer	PEFC controlled sources	Spruce or Pine
Tongue and groove	Length	1,35 mm
	Width	Uniclic

Surface layer

Wood species	Oak
Origine	Europe
Finishing	Matt / Satin lacquer

Installation

Floating	On Pergo underlay	CF installation instructions
Glued to subfloor	Pergo MS polymere resin	CF installation instructions

Warranty

Domestic use	Conditions in each pack	33 years
Uniclic connection		Lifetime
Commercial		On request

Finishing

UV curing varnish		5 - 7 layers
Wear resistance	SIS 923509	Falling sand
	DIN 68861	S 33
Scratch resistance		Anti-scratch top coat
Stain resistance	EN 13442	All except blue ink
		Blue ink
CE	EN 14342: 2008-09	DOP PW 0501
Castor chairs		Use soft castors, type W (EN 12529) and/or suitable office mat
Slip resistance	CEN/TS 15676	USRV 48-52
Emission of formaldehyde	EN 717-1	E1
PCP		below detection limit
Heat resistance	EN 12664	0,127 m ² .KW
Underfloor heating	Suitable	CF special installation instructions
Reaction to fire	EN 14342	CWFT
		CF-s1

Ecological certificates

U-zeichen	Z.156.606-898
AFFSET	A
PEFC	PEFC/07-32-37
M1	OK
EPD	On request

