

TECHNICAL DATA SHEET

Pergo Jomfruland

Edition

03.2016



General data

| | | | |
|----------------------------|---------------------|--|--|
| Panel | 2200 x 190 mm | | |
| Total thickness | 14 mm | | |
| Numbers of panels per pack | 6 | | |
| m ² per pack | 2,51 m ² | | |

Panel build up

| | | | |
|-------------------|-------------------------|-----------------------------|---------|
| Toplayer | PEFC controlled sources | 3,2 mm | |
| Core board | Spruce | | |
| Backing layer | PEFC controlled sources | Spruce or Pine | 1,35 mm |
| Tongue and groove | Length | Uniclic | |
| | Width | Perfect Fold 3.0 Connection | |

Surface layer

| | | | |
|--------------|----------------------------------|--|--|
| Wood species | Oak | | |
| Origine | Europe | | |
| Finishing | UV-hardening oil / Sidematt lack | | |

Installation

| | | |
|-------------------|-------------------------|------------------------------|
| Floating | On Pergo underlay | CF installation instructions |
| Glued to subfloor | Pergo MS polymere resin | CF installation instructions |

Warranty

| | | |
|--------------------|-------------------------|----------|
| Domestic use | Conditions in each pack | 33 years |
| Uniclic connection | Lifetime | |
| Commercial | On request | |

Finishing

| | | | |
|--------------------------|--|--------------------------------------|------------|
| UV curing varnish | 5 - 7 layers | | |
| Wear resistance | SIS 923509 | Falling sand | 800 - 1000 |
| | DIN 68861 | S 33 | 100 - 1050 |
| Scratch resistance | Anti-scratch top coat | | |
| Stain resistance | EN 13442 | All except blue ink | class 5 |
| | | Blue ink | class 3 |
| CE | EN 14342: 2013 | DOP PCO 0501 | |
| Castor chairs | Use soft castors, type W (EN 12529) and/or suitable office mat | | |
| Slip resistance | CEN/TS 15676 | USRV 50-52 | |
| Emission of formaldehyde | JIS A5108 | F4 Star | |
| PCP | below detection limit | | |
| Heat resistance | EN 12664 | 0,14 m ² /KW | |
| Underfloor heating | Suitable | CF special installation instructions | |
| Reaction to fire | EN 14342 | CWFT | Dfl-s1 |

Ecological certificates

| | |
|-----------|---------------|
| U-zeichen | Z.156.606-898 |
| AFFSET | A |
| PEFC | PEFC/07-32-37 |
| EPD | On request |

